BLUE ENERGY

- Maintenance free
- Multi-protection for safety
- Constant power
- Long cycle life and superior performance
- Compact size & easy to install
- Easy to scale up
- Compatible with tier 1 inverter brands
- Non hazardous

BEP-8000

Basic Parameters

SKU: BEP-8000
DC Voltages – Nominal: 25.6Vdc
Amps-Hours: 314Ah
Maximum Rated kWh Capacity:
8,038Wh @ 100% DOD
6,430Wh @ 80% DOD
Dimensions (H*W*D) mm: 620 x 400 x 250
Weight: 66Kg | 146Lbs
Maximum Discharge Rates (10mn): 150A DC / 3.6kW DC
Maximum Continuous Discharge Rate: 100A DC / 2.4kW DC
Maximum Continuous Charge Rate: 100A DC / 2.4kW DC
DC Voltage Range: 24Vdc to 28Vdc
Depth of Discharge (DOD): Up to 100% / Recommend 80%
Charging Temperature: 0 to 120 ℉ / 0 to 49 ℃
Operating Temperature: -4 to 140 ℉ / -20 to 60 ℃
Shelf Temperature:
6 Months: 14 to 77 ℉ / -10 to 25 ℃
3 Months: -4 to 113 ℉ / -20 to 45 ℃
Self-Discharge Rate: < 1% per month
Cooling Type: Natural
Communication: RS485, CAN
Configuration (Max in 1 battery group): 16 pcs
Design Life: 15 + years (25℃/77℉)
Cycle Life: > 7000 - Cycles at 70% SOH
RTE Efficiency: 97%
Warranty: 5 Year

OTHER PRODUCTS

BEP-1200

BEP-16000

CONTACT US

www.BlueEnergyPower.com
info@BlueEnergyPower.com
@blue_energy_power